

### General Series Battery

FM series batteries are Maple Armor brand universal lead-acid batteries. Using high-quality lead calcium multi-element alloy plates, with high rate discharge capacity; High performance cast welded grid, with conductivity 30% higher than ordinary batteries; Internally, it adopts integrated casting and welding, reducing internal resistance by 20% and better adapting to high current discharge; Unique AGM technology enables higher energy density and stronger charging acceptance of batteries; Imported ABS raw materials and self-made shell, using self-developed automatic sealing technology, make the battery a complete whole, greatly improving sealing performance; Copper terminals (plug-in/vertical/downward rotation) not only meet the needs of high current charging and discharging, but also have flexible installation and more convenient maintenance. This series of batteries is manufactured using internationally advanced automated production lines, with high stability and consistency, and a longer service life. Design lifespan up to 5 years (25 °C)

#### Application

- \* Emergency Power System
- \* Communication equipment
- \* Telecommunication systems
- \* Uninterruptible power supplies
- \* Electric toy car and wheelchairs, etc.
- \* Power tools
- \* Alarm system
- \* Marine equipment
- \* Medical equipment
- \* Fire and Security System



#### General Features

- \* Heavy Duty Grid
- \* Mechanized assembly
- \* Non-spillable construction
- \* High Reliability and Stability
- \* Sealed and Maintenance-free
- \* Long Life and low self-discharge design

#### Construction


- \* Positive ..... Lead dioxide
- \* Electrolyte ..... Sulfuric acid
- \* Separator ..... Fiber glass
- \* Negative ..... Lead
- \* Safety Valve ..... EPDR
- \* Terminal ..... Copper
- \* Container ..... ABS(UL94-HB) / Flame Retardant ABS (UL94-V0)

#### Specification

Battery Model	Nominal Voltage		12V (6 cells per unit)	
	Rated capacity (20 Hour rate)		7Ah	
Dimension	Length	Width	Height	Total Height
	151mm (5.94 inches)	65mm (2.56 inches)	94mm (3.70 inches)	100mm (3.94 inches)
Approx Weight	1.99kg(4.38 lbs) ± 3%			
Internal Resistance	Full charged at 25°C(77°F): Approx 26.0mΩ			
Maximum Charge Current	2.10A			
Max. discharge current	105A (5Sec.)			
Short-circuit current	255A			
Operating Temperature Range	Nominal Operating Temperature 25°C(77°F)	Discharge -15°C~50°C(5°F~122°F)	Charge -15°C~40°C(5°F~104°F)	Storage -15°C~40°C(5°F~104°F)
Capacity @ 25°C (77°F)	20 hour rate(0.36A,10.5V) 7.20Ah	10 hour rate(0.67A,10.5V) 6.70Ah	5 hour rate(1.19A,10.5V) 5.95Ah	1 hour rate(4.46A,9.6V) 4.46Ah
Capacity affected by Temp.(20HR)	40°C (104°F) 102%	25°C (77°F) 100%	0°C (32°F) 85%	-15°C (5°F) 65%
Charge method	Float Charging Voltage 13.5 ~ 13.8 VDC/Unit at 25°C(77°F)		Cycle Use Charging Voltage 14.4~ 15.0 VDC/Unit at 25°C(77°F)	

#### Outer dimension (mm)

#### Terminal Type



#### Constant Current(Amp) and Constant Power(Watt) Discharge Table at 25°C(77°F)

F.V/Time	5min	10min	15min	20min	30min	1h	2h	3h	5h	8h	10h	20h
1.85V/cell	A	20.1	14.3	10.8	8.75	6.61	3.98	2.41	1.76	1.150	0.750	0.639
	W	37.7	27.0	20.6	16.73	12.80	7.86	4.79	3.55	2.310	1.510	1.290
1.80V/cell	A	21.7	15.2	11.4	9.23	6.79	4.04	2.45	1.79	1.170	0.770	0.651
	W	39.9	28.0	21.5	17.23	13.45	8.17	4.85	3.61	2.340	1.530	1.305
1.75V/cell	A	22.9	15.9	11.8	9.51	7.01	4.16	2.50	1.82	1.190	0.780	0.670
	W	42.3	28.9	22.2	17.75	13.89	8.33	4.93	3.66	2.370	1.550	1.323
1.70V/cell	A	24.0	16.5	12.2	9.87	7.18	4.25	2.55	1.85	1.210	0.790	0.673
	W	44.1	29.7	22.9	18.29	14.25	8.44	5.02	3.70	2.400	1.570	1.328
1.67V/cell	A	24.9	16.9	12.5	10.11	7.31	4.31	2.59	1.87	1.220	0.800	0.676
	W	45.4	30.6	23.4	18.67	14.53	8.52	5.09	3.73	2.420	1.590	1.336
1.60V/cell	A	26.9	17.9	13.1	10.49	7.67	4.46	2.65	1.91	1.240	0.810	0.678
	W	47.6	32.2	24.1	19.32	14.65	8.63	5.17	3.77	2.450	1.610	1.345

